



The Jalasoft Smart Management Pack for APC UPS delivers enterprise ready monitoring of your network environment. You can monitor your network proactively and be aware of any potential problems that might occur, verify the status of your interfaces and ports, CPU load, traffic and much more.

All information is forwarded efficiently to Microsoft System Center Operations Manager 2007 which creates a one stop interface to see the status of your servers and network infrastructure.

Alerts and performance data are visible in **OpsMgr 2007** and will help you take action and prevent any downtime.

A large number of **pre-defined** rules are provided with the Jalasoft Smart Management Pack for APC UPS. Installation is quick and simple and starting to monitor your network is just a matter of dragging and dropping the rules on the specific devices.

This is made possible through the use of Xian Network Manager Io, the platform that runs the Smart Management Pack; no complicated programming or scripting is needed. You can also configure syslog filters to forward syslog alerts to OpsMgr 2007 and monitor single interfaces as an object, simplifying the monitoring of devices with distributed applications.


In order to analyze the behavior of the network device for a longer period of time, the APC UPS Smart Management Pack has a set of reports that can be executed from the OpsMgr 2007 Reporting Console.

Rule Parameters

An easy wizard lets you configure the rule parameters. All rules have by default three steps: rule parameters, active rule options and schedule.

Parameters

You can configure when an alert will be sent to OpsMgr 2007. In many cases, this will be when the value is over or under a certain threshold.



However, for status based rules you can choose to generate an alert when the status changes or when it becomes a certain value (e.g. interface operational status: up, down, testing, unknown, or dormant).

For those rules related to interfaces, it is possible to select the interfaces where you want to apply the rule and define their individual thresholds. This way you can fine-tune the Xian environment.

Active rule options

The severity level is sent to OpsMgr 2007 when a rule meets the selected criteria.

OpsMgr 2007 organizes the alerts by severity. With this option you can predefine each alert with a different level of severity (debug, informational, warning, error or critical), define the collection of performance counters to be used in performance data views or Xian Reports, rename the rule, and enable debug mode for the active rule.

Schedule

You can set the interval between each execution of the rule. This can vary within a range of seconds, minutes or days. When setting this step take into account that a short interval will consume more system resources.

Rules

APC UPS performance and status rules¹

General

- Attempt failed TCP connections
- Defective battery packs
- Device availability
- Established TCP connections
- Open active TCP connections
- Open TCP connections
- System uptime
- Test diagnostic results
- UDP open ports
- UPS Agent communication status
- UPS output load
- UPS status

Interface

- Failed reassembly requests
- Fragmentation failed
- Fragments created
- Incoming discarded packets
- Incoming error packets
- Incoming segments
- Incoming traffic
- Interface operational status
- Outgoing discarded packets
- Outgoing error packets
- Outgoing segments
- Outgoing traffic
- Reassembly requests
- Total discarded packets
- Total error packets
- Total segments
- Total traffic

Battery

- Battery replace indicator status
- Battery run time remaining
- Battery temperature
- Time on battery power
- UPS batteries status

Power

- Last input fail cause
- Maximum input voltage
- Minimum input voltage

Supported Devices

The Xian Io Smart Management Pack for APC UPS supports the following models:

Smart UPS:

Smart UPS 250
Smart UPS 400
Smart UPS 600
Smart UPS 900
Smart UPS 1250
Smart UPS 2000
Smart UPS 450
Smart UPS 700
Smart UPS 1000
Smart UPS 1400
Smart UPS 2200
Smart UPS 3000
Smart UPS 5000

Matrix model:

Matrix UPS
Matrix UPS 3000
Matrix UPS 5000

Symmetra model:

Symmetra UPS 4kVA
Symmetra UPS 8kVA
Symmetra UPS 12kVA
Symmetra UPS 16kVA
Symmetra 3 Phase UPS:
Symmetra 3 Phase UPS 40kVA
Symmetra 3 Phase UPS 60kVA
Symmetra 3 Phase UPS 80kVA
Symmetra 3 Phase UPS 20kVA

AIS 5000 UPS:

Ais 5000 UPS 10kVA
Ais 5000 UPS 20kVA
Ais 5000 UPS 30kVA
Ais 5000 UPS 40kVA
Ais 5000 UPS 60kVA
Ais 5000 UPS 80kVA
Ais 5000 UPS 100kVA

¹ Some rules may not be applicable to specific device models.

Smart UPS 3 Phase:

Smart UPS 3 Phase 10kVA
Smart UPS 3 Phase 15kVA
Smart UPS 3 Phase 20kVA
Smart UPS 3 Phase 30kVA
Smart UPS 3 Phase 40kVA

If you want to obtain the updated list of supported devices or if you are interested in adding support for new models, please write to techsupport@jalasoft.com.

System Requirements

Minimum requirements to install Xian Io Smart Management Pack for APC UPS for Microsoft System Center Operations Manager 2007 are:

- Xian Network Manager Io Platform
- Microsoft Windows Server 2003 SP1 or higher
- Microsoft SQL Server 2000 SP4 or Microsoft SQL Server 2005 SP1 or higher
- Microsoft .NET Framework 3.0.
- MDAC 2.8 SP1 or higher
- SNMP connectivity to all managed devices
- Microsoft System Center Operations Manager 2007
- MS Messaging Queuing
- SQL Server Reporting Services 2005
- Operations Manager Reporting 2007

Contact Info

Jalasoft Corporation
Houston Headquarters
1219 Durham
Houston, Texas 77007
www.jalasoft.com

Phone 1-(888) 402-6717
Fax 1-(408) 463-6155

Sales

sales@jalasoft.com

Partner Support

partners@jalasoft.com

Marketing Support

marketing@jalasoft.com

Technical Support

techsupport@jalasoft.com